

PARTS BREAKDOWN FOR SPEAKER 19C320302G1-G12
LBI4488D

SYMBOL	GE PART NO.	DESCRIPTION
----- LOUDSPEAKERS -----		
LS1	19A116604P1	Permanent magnet: 5 inch, 8 ohms +10% imp, 20 w. max operating; sim to Oaktron 5EU2189-2. (Used in G1, G6, & G8).
LS2	19A116910P1	Permanent magnet: 5 inch, 3.2 ohms +15% imp, 5 w. max operating; sim to Pioneer 002009. (Used in G2-G5, G7, G9-G12).
----- CABLES -----		
W1	19A129414G1	2 conductor cable: approx 5 feet long, includes (2) 19A116781P5 contacts. (Used in G1, G9-G12).
W2	19A122167G1	Cable assembly: approx 4 feet long. (Used in G2, G5, & G8). Includes:
P702	5493018P2	Plug: 5 contacts, sim to Cinch 204-31-05-010.
	5491563P4	Cover; sim to Methode C8C0-V.
W3	19A121546G1	Cable: approx 4 feet long. (Includes (2) 19A121429P1 pins - Used in G3 & G4).
W4	19A130648G1	Cable assembly: approx 5 feet long. (Used in G6). Includes:
P1		Connector. Includes:
	19B209288P16	Shell.
	5496809P18	Contact, electrical. (Quantity 2).
W5	19A136574G1	Cable assembly: approx 4 feet long. Includes (2) 19A115884P8 contacts.
----- MISCELLANEOUS -----		
	19B219692G1	Grille. (Used in G1, G4-G7, & G10).
	19B219692G2	Grille. (Used in G2, G8, & G9).
	19B219692G3	Grille. (Used in G3).
	19B219692G4	Grille. (Used in G11).
	19B219692G5	Grille. (Used in G12).
	19B227593G1	Housing. (Used in G1, G4-G7, & G10).
	19B227593G2	Housing. (Used in G2, G8, & G9).
	19B227593G3	Housing. (Used in G3).
	19B227593G4	Housing. (Used in G11).
	19B227593G5	Housing. (Used in G12).
	19C320016P1	Mounting bracket. (Located between housing & retaining bracket).
	19C320022P1	Retaining bracket. (Located between mounting bracket & safety release disc).
	19B219578G1	Safety Release Disc.
	19A116086P10R	Screw, thread forming, assembled washer: Phillips POZIDRIVE, HI-LO thread, No. 7-19 x 1/2. (Secures speaker to housing).
	19A116086P112	Screw, thread forming, assembled washer: Phillips POZIDRIVE, HI-LO thread, No. 7-19 x 3/4. (Secures grille to housing).
	N187P16010C6	Machine screw: No. 10-32 x 5/8. (Secures mounting bracket to housing - Used with safety release disc, retaining bracket).
	N710P16012C6	Screw, hexhead, slotted: No. 10-16 x 3/4. (Quantity 3 - Used without safety release disc & retaining bracket).
	N187P16010C6	Machine screw, slotted: No. 10-32 x 5/8. (Used with safety release disc & retaining bracket).
	N130P16012C6	Tap screw, thd. forming: No. 10-16 x 3/4. (When mounting to regular surface).
	N130P16024C6	Tap screw, thd. forming: No. 10-16 x 1-1/2. Slotted hex head. (When mounting to extra thick mounting surface).

*COMPONENTS ADDED, DELETED OR CHANGED BY PRODUCTION CHANGES

GENERAL ELECTRIC COMPANY • MOBILE COMMUNICATIONS DIVISION
WORLD HEADQUARTERS • LYNCHBURG, VIRGINIA 24502 U.S.A.