

PARTS LIST
CONTROL UNIT TABLE MOUNT
MODEL 4EC39A10, REV. B
PL-5498721-G1

<u>Symbol</u>	<u>G-E Part No.</u>	<u>Description</u>
<u>LAMPS</u>		
I701 and I702	19B201122-P1	Lamp, midget screw base, 6-v. 200-ma. G-E No. 1768. Included in XI701 and XI702.
<u>CONNECTORS</u>		
J701	7117934-P2	Chassis connector, 4 female contacts Amphenol 91-PC4F.
<u>LOUDSPEAKERS</u>		
LS701	7487536-P1	Speaker, permanent magnet, 3-1/2" voice coil imp, 3.2 ohm $\pm 10\%$, cone resonance 200- to 325-cps, 2-w.
<u>PLUGS</u>		
P701	7144137-P1	21 Female contacts. Sim to HB Jones S-321.
P702		Included in W702.
P703 and P704		Included in W701.
P705	2R22-P4	Junction connector. Sim to Amphenol 83-1J.
<u>RESISTORS</u>		
R701	3R77-P222K	Composition, 2200 ohms $\pm 10\%$, 1/2-w.
R702	5496870-P1	Potentiometer, composition, for push on knob; 15,000 ohms $\pm 20\%$ linear taper. Includes switch, SPST, 6-amps at 125-VAC. Sim to Mallory Controls LC15MP.
R703	5496870-P2	Potentiometer, composition, res. 250,000 ohms $\pm 20\%$, modified log taper. Includes switch (S701); SPST, 6-amps at 125-VAC. Sim to Mallory Controls LC250MPOAC.
R704	3R77-P330K	Composition, 33 ohms $\pm 10\%$, 1/2-w.

<u>Symbol</u>	<u>G-E Part No.</u>	<u>Description</u>
<u>RESISTORS (Cont'd)</u>		
R705	3R77-P470K	Composition, 47 ohms, $\pm 10\%$, 1/2-w.
<u>SWITCHES</u>		
S701		Switch, power - Part of R703
<u>CABLES</u>		
W701	7474980-G37	Antenna lead, consists of plug M2R22P1, and cable 7488600P95, 60" of RG-58 a/n cable, and connector 7104941-P6. Max. op. voltage 350-VRMS, 500-VDC, op. Temp. 80°C.
W702	7130574-P6	Cord set, No. 18-AWG 10 ft. long. with molded plastic plug. Sim to G.E. 2073-1 color-black.
<u>INDICATOR LIGHTS</u>		
XI701	19B201122-P2 19B201122-P3	Socket: Green Lens:
XI702	19B201122-P2 19B201122-P4	Socket: Red Lens:

COMMUNICATION PRODUCTS DEPARTMENT
GENERAL ELECTRIC COMPANY
LYNCHBURG, VIRGINIA