

COMBINATION NOMENCLATURE

Digit 1	Digit 2	Digit 3	Digit 4	Digit 5	Digit 6	Digit 7
Mechanical Package	System Voltage	Frequency Capability	Number of Freq.	Microphone Type	Options	Control Unit Series
W Weatherproof Control Unit (less Acces.)	1 ±12 VDC	A 1-Freq.	A 1-Freq.	1 NONE	S Standard	7 C-700
V Weatherproof Control Unit (MASTR II)	2 ±24 - 48 VDC	C 2-Freq.	C 2-Freq.	2 Weatherproof Microphone	C Dual Control	
Y Weatherproof Control Unit (Exec. II)	3 -12 VDC (Neg. Gnd only)	F 4-Freq.	E 3-Freq.	8 Weatherproof Handset	U Channel Guard Monitor	
	4 -12 VDC (Pos. Gnd only)	K 8-Freq.	F 4-Freq.		E Internal/External Speaker	
		P 12-Freq.	G 5-Freq.		B Dual Control & Chan. Gd. Mon.	
			H 6-Freq.		D Dual Control & Int/Ext. Speaker	
			J 7-Freq.		F Chan. Gd. Monitor Int/Ext. Speaker	
			K 8-Freq.		A Dual Control, Chan. Guard Mon. & Int/Ext. Speaker	
			L 9-Freq.			
			M 10-Freq.			
			N 11-Freq.			
			P 12-Freq.			

OPERATOR'S MANUAL (ALL): LBI30431

Product Code 12
C-700 Series Control Unit

BINDER
MAINTENANCE MANUAL (BLUE)
COMBINATION NO.

ALL

LBI4865/DF4108

C700 CONTROL OPTIONS (PC12)

OPTION	PUBLICATION	DESCRIPTION
9081	None	33 Foot Ground Cable
9100	LBI4865*/DF4108	Fixed Squelch

LEGEND:

NONE= NO INSTRUCTION
*= INSTRUCTIONS
PROVIDED AS PART
OF ASSOCIATED
EQUIPMENT MANUAL

GENERAL ELECTRIC COMPANY • MOBILE COMMUNICATIONS DIVISION
WORLD HEADQUARTERS • LYNCHBURG, VIRGINIA 24502 U.S.A.

GENERAL  ELECTRIC
U.S.A.