

COMBINATION NOMENCLATURE

Digit 1	Digit 2	Digit 3	Digit 4	Digit 5	Digit 6	Digit 7	Digit 8 & 9	Digit 10	Digit 11
Mechanical Package	System Voltage	Power Output	Channel Spacing	Frequency Capacity	Number of Freq.	Options	Frequency Range	Freq. Range	PA Type
C Front Mount	T -12 VDC (Negative Ground Only)	3 1-7 Watts	5 25 kHz	A Single Freq.	A 1-Freq. Tx 1 Freq. Rx	G CG & UHS	88 450-470 MHz	A ±5 PPM	L Low Power
						P UHS	89 470-494 MHz	B ±2 PPM	
						S Standard	91 494-512 MHz		
						U Channel Guard			

Product Code 15
5-WATT CUSTOM MVP MOBILE

OPERATOR'S MANUAL	LBI-30165
BINDER	ECP200
COMBINATION MANUAL (BLACK)	
<u>DIGITS</u>	
ALL	LBI-30163/DF9041
INSTALLATION MANUAL	
<u>DIGITS</u>	
ALL	LBI-30164/DF9041
TRANSMITTER MANUAL (ORANGE)	
<u>DIGITS 8 & 9</u>	
88,89,91	LBI-30393/DF3164
RECEIVER MANUAL (BROWN)	
<u>DIGITS 8 & 9</u>	
88,89,91	LBI-30151/DF1113
SAS MANUAL (DARK BLUE)	
<u>DIGITS</u>	
ALL	LBI-30148/DF4101
CHANNEL GUARD (LIGHT GREEN)	
DIGIT	
7	
U,G	LBI-30370/DF5047 LBI-31128 (AFTER 1/82)

5-WATT CUSTOM MVP MOBILE OPTIONS (PC15)

OPTION	PUBLICATION	DESCRIPTION
1941	LBI 30164* /DF9041	Tilt Mount Adaptor Kit

LEGEND:
NONE= NO INSTRUCTIONS
*= INSTRUCTIONS
PROVIDED AS PART OF
ASSOCIATED EQUIPMENT
MANUAL



GE Mobile Communications