

COMBINATION NOMENCLATURE

Digits 1 & 2	Digit 3	Digit 4	Digit 5	Digit 6	Digit 7	Digits 8 & 9
Product Line	RF Power	Channel Spacing	Mode of Operation	Alert Tone	Options	Frequency Range
PC Personal Pager	O Receive Only	5 25 kHz 6 30 kHz	A Tone & Voice (Automatic) B Tone & Voice (Push-To-Reset) C Tone & Voice (Push-To-Listen) D Tone Only (Push-To-Silence) E (Noise Squelch)	W Fixed Output V Adjustable Output U Noise Squelch	L Type 99 Decoder S Noise Squelch	66 150.8-174 MHz 88 450-470 MHz

Issue 2

June 1980

11000-6 (PC51)

**PUBLICATION INDEX
PERSONAL PAGER (PCO)**

PRODUCT CODE 51
PERSONAL PAGER (PCO)

OPERATOR'S MANUAL

LBI4210

MAINTENANCE MANUAL

DIGIT 8

DIGIT 9

6
8

6
8

LBI4200/DF1099

LBI4221/DF1099

PERSONAL PAGER (PCO) OPTIONS (PC51)

OPTION	PUBLICATION	DESCRIPTION
4213	LBI4200*/DF1099 LBI4221*	Indoor Antenna
5400	None	Band End Trim Modification
5401	None	Delete Nickel Cadmium Battery
5402	LBI4200*/DF1099 LBI4221*	Mercury Battery Pack (12)
5403	LBI4200*/DF1099 LBI4221*	Nickel Cadmium Battery
5404	LBI4200*/DF1099 LBI4221*	Alkaline Battery (6)
5405	LBI4217/DF0068	Desk Charger
5406	LBI4217/DF0068	Desk Charger w/Ext. Ant. & Battery Charger
5407	LBI4217/DF0068	Multi-Charger 4EP74A10 (15 Receivers)
5408	LBI4217/DF0068	Multi-Charger 4EP74A11 (10 Receivers, 5 Batteries)
5409	LBI4217/DF0068	Multi-Charger 4EP74A12 (5 Receivers, 10 Batteries)
5410	LBI4217/DF0068	Multi-Charger 4EP74A13 (15 Batteries)
5413	LBI4225/DF0068	Vehicular Charger 4EP75A10
5415	LBI4200*/DF1099 LBI4221*	Black Leather Case
5417	LBI4200*/DF1099 LBI4221*	Belt Mount for Radio
5420	LBI4200*/DF1099 LBI4221*	Lapel Speaker
5421	LBI4200*/DF1099 LBI4221*	Earpiece
5422	LBI4225/DF0068	5-Watt Vehicular Speaker
5424	None	Nickel Cadmium Battery (UL Approved)
5425	LBI4228/DF10008	Test Fixture 4EX17A10

GENERAL ELECTRIC COMPANY • MOBILE COMMUNICATIONS DIVISION
WORLD HEADQUARTERS • LYNCHBURG, VIRGINIA 24502 U.S.A.

GENERAL  ELECTRIC*
U.S.A.