



PUBLICATION INDEX

MASTR® EXECUTIVE II VEHICULAR REPEATER

COMBINATION NOMENCLATURE

DIGIT 1	DIGIT 2	DIGIT 3	DIGIT 4	DIGIT 5	DIGIT 6	DIGIT 7
Mechanical Package	System Voltage	Control	Power Output	Channel Spacing	Frequency Range	Options
M Used with MASTR II Comb.	V +12 VDC (Negative Ground only)	R Prioritizing	I 0-9 Watts	5 25 KHz	G 138-155 MHz	S None
E Used with Executive II Comb.				6 30 KHz	H 150.8-174 MHz	N Noise Blkr.
D Used with DELTA-S/SX and RANGR					K 406-420 MHz	P Pre-Amp
R RANGR Application (CHP)					M 450-470 MHz	
					N 470-494 MHz	
					P 494-512 MHz	

OPERATORS MANUAL: LBI-30831

PC82
MASTR EXECUTIVE II
VEHICULAR REPEATER

BINDER
COMBINATION MANUAL (BLACK)
DIGIT 1
M, E, D

R
INSTALLATION MANUAL
DIGIT 1
M, E
D
R

TRANSMITTER MANUAL (ORANGE)
DIGIT 6
K, M, N, P
G, H

RECEIVER MANUAL (BROWN)
DIGIT 6 DIGIT 7
G, H S, P
G, H N
K, M, N, P -

SYSTEM BOARD (BLUE)
DIGIT 1
M, E, D
R

LOGIC BOARD
DIGIT 1
M, E, D, R

CHANNEL GUARD
DIGIT 1
M, E, D
TYPE 90
DIGIT 1
M, E, D, R

ECP200

LBI-31154/DF9051
(LBI-30830 - Earlier models)
LBI-38148

LBI-30115/DF9040
LBI-31031
LBI-38147

LBI-30818/DF3163
LBI-30815/DF3163

LBI-30055/DF1112
LBI-30056/DF1112
LBI-30062/DF1112

LBI-30827/DF4101
LBI-38149

LBI-31159/DF9051
(LBI-30824 - Earlier models)

LBI-4870/DF5044

LBI-30814/DF5044

OPTIONS

<u>OPTION</u>	<u>PUBLICATION</u>	<u>DESCRIPTION</u>
2701	LBI-30853/DF9051	Over/Under Mount (MASTR II Only)
2703	LBI-4870/DF5044	Mobile Channel Guard Decoder
2704-A	LBI-4689/DF1102	Mobile Detector 30-36 MHz
2704-B	LBI-4689/DF1102	Mobile Detector 36-42 MHz
2704-C	LBI-4689/DF1102	Mobile Detector 42-50 MHz
2704-D	LBI-30188/DF1115	Mobile Detector 66-76 MHz
2704-E	LBI-30188/DF1115	Mobile Detector 75-88 MHz
2704-G	LBI-4664/DF1102	Mobile Detector 138-150.8 MHz
2704-H	LBI-30035/DF1102	Mobile Detector 150.8-174 MHz
2704-K	LBI-4639/DF1116	Mobile Detector 406-420 MHz
2704-M	LBI-4639/DF1116	Mobile Detector 450-470 MHz
2704-N, P	LBI-4642/DF1102	Mobile Detector 470-512 MHz
2705	LBI-30814/DF5051	Alternate Selective Amplifier

