

PUBLICATION INDEX M-PD PERSONAL COMBINATION NOMENCLATURE

DIGITS 1 & 2	DIGIT 3	DIGIT 4	DIGIT 5	DIGIT 6	DIGIT 7
Product Code	Frequency	Controller	Selectivity	Stability	Power Source
PD	G 136-160 MHz	A Standard	S Standard	2 2.5 PPM	N 800 MAH NICD
	H 150-174 MHz	B 4 Button	N 12.5 KHz	5 5 PPM	M 1200 MAH NICD
	P 403-423 MHz	C System			X No Battery
	R 410-430 MHz				
	S 420-440 MHz				
	T 440-460 MHz				
	U 450-470 MHz				
	V 470-488 MHz				
	W 482-500 MHz				
	X 494-512 MHz				
	Z 808-870 MHz				

STRUCTURED OPTIONS

A Programming	F Option
1 Factory	0 None
2 Customer	4 Int. Safe Grp. C

INSTALLATION AND MAINTENANCE MANUALS

MAINTENANCE MANUAL

OPERATOR'S MANUAL

DIGIT 4

A
B
C

LBI-31624
LBI-31625
LBI-31626

BINDER

ECP-200

COMBINATION MANUAL (BLACK & WHITE)

DIGIT 3

H,G
H,G
H,G
P,R,S,T,U,V,W,X
P,R,S,T,U,V,W,X
P,R,S,T,U,V,W,X
Z
Z
Z

DIGIT 4

A
B
C
A
B
C
A
B
C

LBI-31627
LBI-31628
LBI-31629
LBI-31631
LBI-31691
LBI-31633
LBI-31632
LBI-31692
LBI-31634

Copyright © September, 1986, General Electric Company

GENERAL ELECTRIC COMPANY • MOBILE COMMUNICATIONS DIVISION
WORLD HEADQUARTERS • LYNCHBURG, VIRGINIA 24502 U.S.A.

GENERAL  **ELECTRIC***
U.S.A.

* Trademark of General Electric Company U.S.A.
Printed in U.S.A.