R.F. SECTION

V.C.O.

I.F.SECTION

P.L.L. SYNTHESIZER

MICRO-PROCESSOR

CTCSS MODULE

VOLTAGE REGULATORS

4 KHz LOW PASS FILTER

300 Hz HIGH PASS FILTER

240 Hz NOTCH FILTER

250 Hz LOW PASS FILTER

455 KHz LIMITER/DISCRIMINATOR

2nd OSCILLATOR/MIXER

CHANNEL FILTER

LINE OUTPUT AMP.

MONITOR SPEAKER AMP.

NOISE AMPLIFIER

NOISE FILTER

NOISE DETECTOR

RS-232 INTERFACE

SYSTEM CONNECTOR

TEST CONNECTOR

OPTIONAL REAR PANEL CONNECTOR

CHANNEL SELECT SWITCHES
SET TO 00 WHEN USING AN EXTERNAL SWITCH

CHANNEL DISPLAY/SELECT OPTION

STANDARD 5 PPM OSCILLATOR

OPTIONAL 1PPM TCXO

* VALUES ARE FOR 25 KHZ CHANNEL SPACING

FOR 12.5 KHZ VERSIONS
R15 470
R24 33K
CF1 CFS455G

Use C189 on R71A
Use L2 on R70, and R150 Series

NB. C189 and L2 occupy the same SMD location.

I.F. AMPLIFIERS AND CRYSTAL FILTERS
Note that model R71A has a 21.4 Megahertz IF.
The R70 and the R150 Series have a 45 MHz IF.

HPF IN/OUT

NOTCH IN/OUT

DE-EMPHASIS / FLAT

MONITOR SQ. ON/OFF

LINE LEVEL

MONITOR VOLUME

LOUDSPEAKER

COS NORM./REV.

DECODE BW

** COMPONENT VALUE TABLE

| FREQUENCY RANGE | Product | C8 | C11 | C12 | C16 | C17 | C18 | C19 | C22 | C23 | C24 | C42 | C45 | C46 | C50 | C60 | C165 | C169 | C172 | C173 | C174 | C175 | C177 | C178 | C179 | | C189* | L2* | L3 | L4 | L5 | L6 | L7 | L8 | L9 | | L13 | L15 | L28 | L29 | L30 | L31 | L32 | L34 | L35 | L36 | L37 | L38 | L39 | L40 | L41 | | R1 | R3 | R7 | R11 | R13 | R48 | R49 | R66 | R70 | R166 | XF1 | XF2 | Y1 | | | | | | | | | | | | | | | | Rev. Level |
|---|---|---